

NEW



## NEW VERSION 10 MM ROPE | ADJUSTABLE WORK POSITIONING LANYARD

Brand new work positioning device enables quick and accurate adjustment of length for positioning at the work station. Super smooth adjustment even under load.

Trimmer is the smallest and lightest length adjustment device on the market!

Features of the new Trimmer+ version

- Reduction of the diameter of the rope from 11 mm to 10 mm improving performance and fluidity of regulation.
- Tested in accordance with EN358: 18 for use up to 150Kg
- New compact and ergonomic terminals with rubber protections, with label and integrated NFC chip to ensure quick and safe identification of the serial number.
- Reduction of the overall dimensions of the terminal head through the use of a sleeve which ensures the loads required by the standard but makes the device more compact and expanding its adjustment range.

Main features:

- The TRIMMER is a incredibly smooth device for progressive adjustment of the lanyard length.
- It is used on the work positioning "D" rings on the harness waistbelt: the length is adjusted by pressing the ergonomic lever.
- Can be used from the ventral or lateral attachment points to adjust the distance from the anchoring point.
- Fitted with protective sheath to protect the rope from the contact points .
- Visible stitchings for a quick visual inspection.
- Lightweight and compact.
- Available in 5 lengths: 1.3, 2, 3, 4 e 5 m
- Other lengths available on request.
- It is possible to install any Kong connector.
- Available in kit with Tango connector already assembled.
- High quality product, completely made in Italy!

Also available Trimmer+ Nude without rope inserted # 80206NO00KK



## Usage activities

SCAFFOLDING AND TRESTELS

ROOF AND INCLINED PLANES

METAL STRUCTURES

ROPE ACCESS

LADDERS AND ELEVATING PLATFORMS

WIND TURBINES

## ITEM CODES

Item	Standards	◀▶(kN)	Length (m)	▲(g)	Rope diameter (mm)	Length regulator
289S00130KK	EN 358	/	1.3	280	10	Yes
289S00200KK	EN 358	/	2	340	10	Yes
289S00300KK	EN 358	/	3	420	10	Yes
289S00400KK	EN 358	/	4	500	10	Yes
289S00500KK	EN 358	/	5	580	10	Yes
289SETS01KK	EN 358	/	2 + Tango	475	10	Yes
289SETS02KK	EN 358	/	3 + Tango	555	10	Yes
289SETS03KK	EN 358	/	4 + Tango	635	10	Yes
289SETS04KK	EN 358	/	5 + Tango	715	10	Yes

Copyright © KONG spa | P.IVA 00703180166

Via XXV Aprile, 4 23804 Monte Marenzo (LC) Italy | Tel. +39 0341 630506